

Product name	HOSTAFORM® FK 1:25 14 BLACK	Revision Date	TNA/EN
MSDS number	8721000093	Issuing date	Aug.20.2012
Revision Number	0.01		Aug.20.2012

1. Identification of the substance/preparation and of the company/undertaking

Product name	HOSTAFORM® FK 1:25 14 BLACK
Material Number:	21000093
MSDS ID	HF1013

Manufacturer, importer, supplier

TICONA
8040 Dixie Hwy.
Florence, KY 41042
United States
<http://www.ticona.com>

Transportation emergency phone numbers:
In USA, call 800-424-9300
Outside USA, call 703-527-3887, collect calls accepted

Product Information
1-800-833-4882
prodinfo@ticona.com

Synonyms:
Acetal copolymer
Polyoxymethylene copolymer

End Use:
Plastic processing industry.

2. Hazards identification

Emergency Overview

Dust from this product can form an explosive organic dust cloud.
Spilled pellets may present a slipping hazard.
The molten product can cause serious burns.

Potential health effects

Immediate effects

Skin	Polymer particles may cause mechanical irritation. The molten product can cause serious burns.
Eyes	Resin particles, like other inert materials, are mechanically irritating to eyes

Product name	HOSTAFORM® FK 1:25 14 BLACK	Revision Date	TNA/EN
MSDS number	8721000093	Issuing date	Aug.20.2012
Revision Number	0.01		Aug.20.2012

Inhalation Overheating in processing may generate hazardous, irritating vapours. Dust irritating to respiratory tract.

Ingestion Low toxicity by this route is expected based on the biological activity of high molecular weight polymers.

Other: Formaldehyde, which is a degradation product, is listed as a potential cancer hazard by OSHA, a known human carcinogen by The International Agency for Research on Cancer (IARC, Group 1), and a substance which can reasonably be anticipated to be a carcinogen by The National Toxicology Program (NTP). Formaldehyde should not pose a risk if exposures are kept below the OSHA Permissible Exposure Limit.

Medical conditions which may be aggravated by exposure: No specific information available on the product. Off-gases, which may be released if overheated, may affect those with chronic diseases of the respiratory system.

3. Composition/information on ingredients

Chemical characterization Polyacetal Copolymer / POM; CAS-RN of the basic polymer: 24969-26-4

Components	CAS-No	Percent %
Carbon black	1333-86-4	1-5
Formaldehyde	50-00-0	Trace level contaminant

This product may contain proprietary ingredients. This is a polymeric material. Any hazardous constituents are wetted by the polymer system, and therefore are unlikely to present exposure under normal conditions of processing and handling.

4. First aid measures

Skin
Cool skin rapidly with cold water after contact with molten polymer. Immediate medical attention is required. Do not peel solidified product off the skin.

Eyes
Immediately flush eye(s) with plenty of water. Call a physician if irritation persists.

Inhalation
Move to fresh air in case of accidental inhalation of vapors. Get medical attention immediately if symptoms occur.

Ingestion
If swallowed, do not induce vomiting - seek medical advice.

Product name	HOSTAFORM® FK 1:25 14 BLACK	Revision Date	TNA/EN
MSDS number	8721000093	Issuing date	Aug.20.2012
Revision Number	0.01		Aug.20.2012

Notes to physician

This product is essentially inert and nontoxic. However, if it is overheated or burns, gases such as carbon monoxide and formaldehyde may be released. Those exposed to off-gases may need to have their arterial blood gases and carboxyhemoglobin levels checked. If the carboxyhemoglobin levels are normal and the exposure occurred in an enclosed space, asphyxia (carbon dioxide replacing oxygen) is a possibility. Formaldehyde is a respiratory irritant gas. If patients may have inhaled high concentrations of irritating fumes they should be monitored for delayed onset pulmonary edema

5. Fire-fighting measures

Suitable extinguishing media

Water, Foam, Dry powder, Gaseous extinguishing media, Dry chemical

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

carbon monoxide
carbon dioxide (CO₂)
Formaldehyde vapours
Hazardous combustion products

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit.

Other Information

Potential dust explosion hazard.

6. Accidental release measures

Personal precautions

Keep away from heat and sources of ignition. Avoid dust formation. Use adequate ventilation.

Environmental precautions

No special precautions required.

Methods for cleaning up

Use mechanical handling equipment. Dispose of in accordance with local regulations.

7. Handling and storage

Handling

Advice on safe handling

Do not handle hot or molten material without appropriate protective equipment. Maintain good housekeeping in work areas. Do not exceed recommended process temperatures to minimize release of decomposition products.

Product name	HOSTAFORM® FK 1:25 14 BLACK	Revision Date	TNA/EN
MSDS number	8721000093	Issuing date	Aug.20.2012
Revision Number	0.01		Aug.20.2012

Protection - fire and explosion

Do not smoke in areas where polymer dust is present. Appropriate measures should be taken to control the generation and accumulation of dust during conveying and processing operations.

Storage

Material storage

Store in a cool dry place. Maintain dryness of resin.

Incompatible products

strong acids oxidizing agents Polyvinyl chloride

8. Exposure controls/personal protection

OSHA Exposure Limits

Components	TWA
Carbon black	3.5 mg/m ³
Formaldehyde	0.75 PPM

ACGIH Exposure Limits

Components	TWA
Carbon black	3.5 mg/m ³

Components	Ceiling Limit Value:
Formaldehyde	0.3 PPM

Components	Manufacturer Workplace Exposure Limit
Formaldehyde	0.75 ppm (TWA); 2 ppm (STEL)

Mexico National Exposure Limits

Components	LMPE - PPT
Carbon black	3.5 mg/m ³

Components	STEL
Carbon black	7 mg/m ³

Components	Mexican Carcinogen Category
Carbon black	A4
Formaldehyde	A2

Product name	HOSTAFORM® FK 1:25 14 BLACK	Revision Date	TNA/EN
MSDS number	8721000093	Issuing date	Aug.20.2012
Revision Number	0.01		Aug.20.2012

Components	Mexican Ceiling Exposure Limit	
Formaldehyde	3 mg/m ³	2 PPM

Exposure controls

Engineering measures

General: May not be adequate as the sole means to control employee exposure.

Local Exhaust: Recommended when appropriate to control employee exposure to dust or process vapors

General advice

Do not breathe dust. Avoid contact with skin and eyes.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment

Skin protection:

When thermal or melt processing, wear long pants, long sleeves, well insulated gloves, and face shield when there is a chance of contact.

Eye/face protection:

safety glasses with side-shields. Safety goggles.

Comments:

Operations involving grinding and machining of parts should be reviewed to assure that particulate levels are kept below recommended standards

Ticona has decided not to adopt the ACGIH TLV for formaldehyde based on a scientific evaluation of all the available data. Ticona has decided to adopt the OSHA Standard. Ticona WEL is the Ticona Workplace Exposure Limit.

9. Physical and chemical properties

Appearance

Form	pellets
Odor	slight , specific .
Flash point	>93°C(>200°F)
Ignition temperature	320°C (608°F)
Method	ASTM D 1929
Density	approx 1.4 - 1.8 g/ml @ 20°C
Bulk density	approx 770 - 890 kg/m ³ @20 °C
Vapor pressure	not determined
Water solubility	insoluble

Product name	HOSTAFORM® FK 1:25 14 BLACK	Revision Date	TNA/EN
MSDS number	8721000093	Issuing date	Aug.20.2012
Revision Number	0.01		Aug.20.2012

10. Stability and reactivity

Reactivity

Stable under normal conditions.

Conditions to avoid

Flame. Do not allow mixing of this material with PVC, other halogen containing materials, and partially and/or fully crosslinkable thermoplastic elastomers. Avoid prolonged heating at or above the recommended processing temperature. Do not heat above 460 °F (238 °C).

Incompatible Materials

strong acids, oxidizing agents, Polyvinyl chloride.

Hazardous Combustion or Decomposition Products:

Trioxane, formaldehyde, paraformaldehyde, formic acid.

Possibility of hazardous reactions

Polyvinyl chloride, Incompatible with strong acids and oxidizing agents.

11. Toxicological information

No data is available on the product itself

12. Ecological information

Ecotoxicity:

The effects of resin pellets on the wildlife that may ingest them is not well understood. In the case of seabirds, some marine biologists believe that the fowl may not be able to pass plastic pellets through their digestive tracts. Thus, large quantities of ingested pellets may cause intestinal blockage, false feelings of satiation or reduction in absorption of nutrients, causing malnutrition and starvation. The goal of SPI's Operation Clean Sweep is zero loss of pellets into the environment.

Environmental Fate/Information:

This material is considered to be non-biodegradable.

13. Disposal considerations

Disposal considerations

Recycling is encouraged. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

This product as shipped is not a RCRA hazardous waste under present EPA regulations

Product name	HOSTAFORM® FK 1:25 14 BLACK	Revision Date	TNA/EN
MSDS number	8721000093	Issuing date	Aug.20.2012
Revision Number	0.01		Aug.20.2012

13. Disposal considerations

14. Transport information

US Department of Transportation Not regulated

TDG Not regulated

Mexico Transport Information Not regulated

ICAO/IATA Not restricted

IMDG Not regulated

15. Regulatory information

U.S. FEDERAL REGULATIONS

TSCA Inventory

This product complies with the U.S. Toxic Substances Control Act (TSCA).

SARA 313 Chemicals

Contains no substances at or above the reporting threshold under Section 313.

CANADIAN REGULATIONS

WHMIS Classification:

Not a WHMIS controlled product.

WHMIS Ingredient Disclosure List IDL:

Carbon Black (1333-86-4)

16. Other information

NFPA:	Health: 1	Flammability: 1	Instability: 0
HMIS:	Health: 1	Flammability: 1	Physical Hazard: 0

Prepared By

Product Stewardship Department
Ticona

Changes against the previous version are marked by ***

Material Safety Data Sheet



Product name	HOSTAFORM® FK 1:25 14 BLACK		TNA/EN
MSDS number	8721000093	Revision Date	Aug.20.2012
Revision Number	0.01	Issuing date	Aug.20.2012

This product is not intended for use in medical or dental implants.

Refer to the appropriate Ticona bulletins for specific processing guidance and good manufacturing practices (purging, processing parameters, shutdown, etc.).

The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. Ticona makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

Abbreviation and Acronym:

IMDG = International Maritime Code for Dangerous Goods

ICAO = International Civil Aviation Organization

IBC Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (IMO)

IATA = International Air Transport Association

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

EINECS = European Inventory of Existing Commercial Chemical Substances

DNEL = Derived No Effect Level

CLP = Classification, Labelling and Packaging

CAS = Chemical Abstracts Service (division of the American Chemical Society)

ADR = Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)